

A/C Refrigerant Oil Tester

The emzone Refrigerant Oil Tester is an innovative product designed to test mobile A/C systems. This visual tester is the ideal tool to identify potential problems, service requirements or whether the system is in good condition.

The tester provides immediate visual results in less than five minutes.

- Checks for sufficient quantity of Refrigerant Lubricant
- Checks the condition of the Refrigerant Oil



Oil Tester
Item Number: 45346


Detailed Instructions

1. Start vehicle.
2. Once cold, run A/C system for 1 minute.
3. Turn vehicle off.
4. Press the single use Oil Tester to low pressure port 3 times.
5. Check color.
(See color strips below).

Locate Low Pressure Port
in vehicle engine compartment.



Low Pressure Port as shown.
Press single use Oil Tester to



Checks for Sufficient Oil In System

COLOR (1)
If capsule colors completely,
A/C System has sufficient oil.



COLOR (2)
If capsule colors only to the
middle, the oil level is too low.
Add lubricant.



COLOR (3)
If capsule colors only a small
amount, Refrigerant A/C oil
must be added without delay.



Checks for Contamination In System

COLOR (1)
Orange, Brown or Black
Flush A/C System and replace with
new oil.



COLOR (2)
Light Brown to Gray
Minimum contamination. Refrigerant Oil
replacement is advisable.



COLOR (3)
White to Yellow Oil quality is
OK. Yellow indicates UV Dye is
present.

